


# Angles

## 6061-T6 American Standard

AMS QQ-A-200/16,  
ASTM B308, AMS 4150  
25' Lengths




A (Inches)	B (Inches)	T (Inches)	Approx WT. Per FT.	Approx WT. Per Length	
.750	.750	.063	.107	2.675	
	.750	.125	.197	4.925	
.875	.875	.125	.234	5.850	
	1.000	.750	.125	.238	5.950
		1.000	.063	.150	3.750
		1.000	.125	.277	6.925
1.250	1.000	.250	.514	12.850	
	1.250	.063	.188	4.700	
	1.250	.125	.351	8.775	
	1.250	.188	.502	12.550	
1.500	1.250	.250	.662	16.550	
	1.500	.125	.389	9.725	
	1.250	.250	.736	18.400	
	1.500	.063	.225	5.625	
	1.500	.125	.424	10.600	
	1.500	.188	.613	15.325	
2.000	1.500	.250	.839	20.975	
	2.000	.125	.497	12.425	
	1.500	.188	.733	18.325	
	1.500	.250	.956	23.900	
	2.000	.125	.578	14.450	
	2.000	.188	.851	21.275	
2.500	2.000	.250	1.087	27.175	
	2.500	.125	.652	16.300	
	2.000	.188	.961	24.025	
	2.000	.250	1.257	31.425	

# Angles

## 6061-T6 American Standard

AMS QQ-A-200/16,  
ASTM B308, AMS 4150  
25' Lengths



A (Inches)	B (Inches)	T (Inches)	Approx WT. Per FT.	Approx WT. Per Length
2.500	2.500	.188	1.072	26.800
	2.500	.250	1.404	35.100
3.000	2.000	.188	1.071	26.775
	2.000	.250	1.403	35.075
	2.000	.375	2.046	51.150
	3.000	.188	1.283	32.075
	3.000	.250	1.684	42.100
	3.000	.375	2.474	61.850
	3.000	.500	3.227	80.675
	3.500	3.500	.250	1.988
3.500	3.500	.375	2.926	73.150
	4.000	3.000	.250	1.989
3.000		.375	2.926	73.150
4.000		.250	2.283	57.075
4.000		.375	3.366	84.150
4.000		.500	4.414	110.350
5.000	3.000	.375	3.35	83.750
	5.000	.375	4.238	105.950
	5.000	.500	5.578	139.450
6.000	4.000	.375	4.237	105.925
	6.000	.500	6.754	168.850
8.000	8.000	.500	9.141	228.525


# Angles

## 6063-T52 Sharp Corners

AMS QQ-A-200/9,

ASTM B221

16' Lengths



A (Inches)	B (Inches)	T (Inches)	Approx WT. Per FT.	Approx WT. Per Length
.500	.500	.063	.068	1.088
	.500	.125	.129	2.064
.625	.625	.125	.165	2.640
	.750	.375	.094	1.824
.750	.500	.125	.165	2.640
	.750	.063	.105	1.680
	.750	.125	.202	3.232
.875	.875	.125	.239	3.824
	1.000	.500	.063	1.680
1.000	.500	.125	.202	3.232
	.750	.125	.239	3.824
	1.000	.063	.141	2.256
	1.000	.125	.276	4.416
1.250	.500	.125	.239	3.824
	1.250	.125	.349	5.584
	1.250	.188	.401	6.416
1.500	1.250	.250	.661	10.576
	.500	.125	.276	4.416
	.750	.125	.312	4.992
	1.000	.125	.349	5.584
1.500	1.500	.125	.423	6.768
	1.500	.188	.622	9.952
	1.500	.250	.808	12.928
	1.750	1.750	.125	.496
2.000	.500	.125	.349	5.584
	.750	.125	.386	6.176


# Angles

## 6063-T52 Sharp Corners

AMS QQ-A-200/9,

ASTM B221

16' Lengths



A (Inches)	B (Inches)	T (Inches)	Approx WT. Per FT.	Approx WT. Per Length
2.000	1.000	.125	.423	6.768
	1.000	.188	.620	9.920
	1.000	.250	.800	12.800
	1.500	.125	.496	7.936
	1.500	.188	.732	11.712
	2.000	.125	.570	9.120
	2.000	.188	.843	13.488
	2.000	.250	1.102	17.632
	2.000	.375	1.586	25.376
2.500	1.000	.125	.496	7.936
	1.500	.125	.570	9.120
	2.000	.125	.630	10.080
	2.500	.125	.717	11.472
	2.500	.250	1.396	22.336
3.000	1.000	.125	.570	9.120
	2.000	.125	.717	11.472
	3.000	.125	.864	13.824
	3.000	.188	1.312	20.992
	3.000	.250	1.690	27.040
3.500	1.250	.125	.680	10.880