


Hexagons


2011-T3 CF
AMS QQ-A-225/3,
ASTM B211
12' Lengths



Size	Decimal	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0656	.7872
5/16	.313	.0373	.4476
3/8	.375	.1488	1.7856
7/16	.438	.2026	2.4312
1/2	.500	.2645	3.174
9/16	.562	.3348	4.0176
5/8	.625	.4133	4.9596
11/16	.688	.4810	5.772
3/4	.750	.5951	7.1412
7/8	.875	.8101	9.7212
1	1.000	1.057	12.684
1 1/8	1.125	1.338	16.056
1 3/16	1.188	1.490	17.88
1 1/4	1.250	1.651	19.812
1 5/16	1.313	1.757	21.084
1 3/8	1.375	1.928	23.136
1 7/16	1.438	2.107	25.284
1 1/2	1.500	2.340	28.08
1 5/8	1.625	2.693	32.316
1 7/8	1.875	3.660	43.92
2	2.000	4.232	50.784

Hexagons

2024-T351, T4 CF
 AMS QQ-A-225/6,
 ASTM B211, AMS 4120
 12' Lengths




Size	Decimal	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0656	.7872
5/16	.313	.1025	1.23
3/8	.375	.1476	1.7712
7/16	.438	.2009	2.4108
1/2	.500	.2624	3.1488
9/16	.562	.3321	3.9852
5/8	.625	.4100	4.92
11/16	.688	.4961	5.9532
3/4	.750	.5904	7.0848
7/8	.875	.8036	9.6432
1	1.000	1.050	12.60
1 1/8	1.125	1.328	15.936
1 1/4	1.250	1.640	19.68
1 3/8	1.375	1.984	23.808
1 1/2	1.500	2.362	28.344
1 5/8	1.625	2.772	33.264
1 7/8	1.875	3.690	44.28
2	2.000	4.198	50.376
1 5/8	1.625	2.730	32.760
1 7/8	1.875	3.690	44.280
2	2.000	4.198	50.370

Hexagons

6061-T6511

AMS QQ-A-200/8,
ASTM B221, AMS 4173
12' Lengths



Size	Decimal	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0660	.792
3/8	.375	.1432	1.7184
1/2	.500	.2600	3.12
3/4	.750	.5729	6.8748
7/8	.875	.7790	9.348
1	1.000	1.018	12.216
1 1/4	1.250	1.591	19.092
1 1/2	1.375	2.292	27.504
1 3/4	1.500	3.119	37.428
2	2.000	4.080	48.96

Hexagons

7075-T6, T651 CF
AMS QQ-A-225/9,
ASTM B211
12' Lengths



Size	Decimal	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0638	.7656
5/16	.313	.0996	1.1952
3/8	.375	.1430	1.716
1/2	.500	.2550	3.06
5/8	.625	.3980	4.776
3/4	.750	.5730	6.876
7/8	.875	.7810	9.372
1	1.000	1.020	12.24
1 1/4	1.250	1.593	19.116
1 1/2	1.500	2.295	27.54
2	2.000	4.080	48.96