


Rounds

2011-T3 CF

AMS QQ-A-225/3, ASTM B211

12' Lengths




SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0601	.7212
5/16	.313	.0939	1.1268
3/8	.375	.1352	1.6224
7/16	.438	.184	2.208
1/2	.500	.2403	2.8836
9/16	.562	.3042	3.6504
5/8	.625	.3755	4.506
11/16	.688	.4544	5.4528
3/4	.750	.5407	6.4884
7/8	.875	.736	8.832
1	1.000	.9613	11.5356
1 1/4	1.250	1.502	18.024
1 5/16	1.313	1.656	19.872
1 3/8	1.375	1.818	21.816
1 1/2	1.500	2.163	25.956
1 5/8	1.625	2.538	30.456
1 3/4	1.750	2.944	35.328
1 7/8	1.875	3.380	40.56
2	2.000	3.845	46.14
2 1/4	2.250	4.867	58.404
2 1/2	2.500	6.008	72.096
2 3/4	2.750	7.270	87.24
3	3.000	8.652	103.824
3 1/4	3.250	10.150	121.8
3 1/2	3.500	11.780	141.36
3 3/4	3.750	13.520	162.24

Rounds

2011-T3 CF

AMS QQ-A-225/3, ASTM B211


12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
4	4.000	15.380	184.56
4 1/4	4.250	17.360	208.32
4 1/2	4.500	19.430	233.16
4 3/4	4.750	21.650	259.80
5	5.000	23.990	287.88

Rounds

2024-T351, T4 CF
AMS QQ-A-225/6,
ASTM B211, AMS 4120
12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0595	.714
5/16	.313	.093	1.116
3/8	.375	.1339	1.6068
7/16	.438	.1822	2.1864
1/2	.500	.238	2.856
9/16	.562	.3012	3.6144
5/8	.625	.3718	4.4616
11/16	.688	.4499	5.3988
3/4	.750	.5354	6.4248
7/8	.875	.7288	8.7456
1	1.000	.9519	11.4228
1 1/4	1.250	1.487	17.844
1 5/16	1.313	1.640	19.68
1 3/8	1.375	1.800	21.60
1 1/2	1.500	2.142	25.704
1 5/8	1.625	2.514	30.168
1 3/4	1.750	2.915	34.98
1 7/8	1.875	3.347	40.164
2	2.000	3.808	45.696
2 1/4	2.250	4.819	57.828
2 1/2	2.500	5.949	71.388
2 3/4	2.750	7.199	86.388
3	3.000	8.567	102.804
3 1/4	3.250	10.050	120.60
3 1/2	3.500	11.660	139.92
3 3/4	3.750	13.390	160.68

Rounds

2024-T351, T4 CF
AMS QQ-A-225/6,
ASTM B211, AMS 4120
12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
4	4.000	15.230	182.76
4 1/4	4.250	17.190	206.28
4 1/2	4.500	19.280	231.36
4 3/4	4.750	21.480	257.76
5	5.000	23.800	285.60
5 1/2	5.500	28.800	345.60
6	6.000	34.270	411.24

Rounds

6061-T6, T651 CF
 AMS QQ-A-225/8,
 ASTM B211,
 AMS 4117
 12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
1/8	.125	.014	.168
3/16	.188	.032	.384
1/4	.250	.057	.684
5/16	.313	.090	1.08
3/8	.375	.129	1.548
7/16	.437	.176	2.112
1/2	.500	.230	2.76
9/16	.562	.292	3.504
5/8	.625	.360	4.32
11/16	.687	.436	5.232
3/4	.750	.519	6.228
7/8	.875	.707	8.484
1	1.000	.924	11.088
1 3/16	1.188	1.302	15.624
1 1/4	1.250	1.44	17.28
1 5/16	1.313	1.591	19.092
1 3/8	1.375	1.746	20.952
1 1/2	1.500	2.078	24.936
1 5/8	1.625	2.439	29.268
1 3/4	1.750	2.829	33.948
2	2.000	3.694	44.328
2 1/4	2.250	4.676	56.112
2 1/2	2.500	5.773	69.276
2 3/4	2.750	6.985	83.82

Rounds

6061-T6, T651 CF
AMS QQ-A-225/8,
ASTM B211,
AMS 4117
12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
3	3.000	8.310	99.72
3 1/4	3.250	9.760	117.12
3 1/2	3.500	11.310	135.72
3 3/4	3.750	12.990	155.88
4	4.000	14.780	177.36
4 1/4	4.250	16.670	200.04
4 1/2	4.500	18.700	224.40
4 3/4	4.750	20.820	249.84
5	5.000	23.090	277.08
5 1/2	5.500	28.000	335.28
6	6.000	33.250	399.00

Rounds

6061-T6511

AMS QQ-A-200/8,
ASTM B211, AMS 4173
12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0577	.6924
5/16	.313	.0901	1.0812
3/8	.375	.1297	1.5564
1/2	.500	.2306	2.7672
9/16	.562	.2922	3.5064
5/8	.625	.3608	4.3296
3/4	.750	.5195	6.234
7/8	.875	.7071	8.4852
1	1.000	.9236	11.0832
1 1/16	1.063	1.043	12.516
1 1/8	1.125	1.169	14.028
1 3/16	1.188	1.302	15.624
1 1/4	1.250	1.443	17.316
1 5/16	1.313	1.591	19.092
1 3/8	1.375	1.746	20.952
1 7/16	1.438	1.909	22.908
1 1/2	1.500	2.078	24.936
1 5/8	1.625	2.439	29.268
1 11/16	1.688	2.630	31.56
1 3/4	1.750	2.829	33.948
1 7/8	1.875	3.247	38.964
2	2.000	3.694	44.328
2 1/8	2.125	4.171	50.052
2 1/4	2.250	4.676	56.112
2 3/8	2.375	5.210	62.52
2 1/2	2.500	5.773	69.276

Rounds

6061-T6511

AMS QQ-A-200/8,
ASTM B211, AMS 4173
12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
2 5/8	2.625	6.364	76.368
2 3/4	2.750	6.985	83.82
2 7/8	2.875	7.635	91.62
3	3.000	8.312	99.744
3 1/4	3.250	9.756	117.072
3 3/8	3.375	10.520	126.24
3 1/2	3.500	11.310	135.72
3 5/8	3.625	12.140	145.68
3 3/4	3.750	12.990	155.88
4	4.000	14.780	177.36
4 1/4	4.250	16.680	200.16
4 1/2	4.500	18.700	224.40
4 5/8	4.625	19.760	237.12
4 3/4	4.750	20.840	250.08
5	5.000	23.090	277.08
5 1/8	5.125	24.260	291.12
5 1/4	5.250	25.460	305.52
5 1/2	5.500	27.940	335.28
5 3/4	5.750	30.538	366.456
6	6.000	33.250	399.00
6 1/4	6.250	36.080	432.96
6 1/2	6.500	39.024	468.288
6 3/4	6.750	42.083	504.996
7	7.000	45.257	543.084
7 1/4	7.250	48.548	582.576
7 3/8	7.375	50.237	602.844

Rounds

6061-T6511

AMS QQ-A-200/8,
ASTM B211, AMS 4173
12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
7 1/2	7.500	51.954	623.448
8	8.000	59.050	708.60
8 1/4	8.250	62.864	754.368
8 1/2	8.500	66.732	800.784
9	9.000	74.814	897.768
9 1/2	9.500	83.357	1000.284
10	10.000	92.363	1108.356
10 1/2	10.500	101.830	1221.96
11	11.000	111.759	1341.108
11 1/2	11.500	122.150	1465.80
12	12.000	133.002	1596.024

Rounds

7075-T6, T651

AMS QQ-A-225/9, ASTM B221,

AMS 4122, AMS 4123

12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
1/4	.250	.0595	.714
5/16	.313	.0930	1.116
3/8	.375	.1339	1.6068
7/16	.438	.1840	2.208
1/2	.500	.2380	2.856
5/8	.625	.3720	4.464
3/4	.750	.5354	6.4248
7/8	.875	.7288	8.7456
1	1.000	.952	11.424
1 1/4	1.250	1.487	17.844
1 5/16	1.313	1.624	19.488
1 3/8	1.375	1.799	21.588
1 1/2	1.500	2.141	25.692
1 5/8	1.625	2.514	30.168
1 3/4	1.750	2.915	34.98
1 7/8	1.875	3.347	40.164
2	2.000	3.808	45.696
2 1/4	2.250	4.819	57.828
2 1/2	2.500	5.949	71.388
2 3/4	2.750	6.988	83.856
3	3.000	8.570	102.84
3 1/4	3.250	10.50	126.00
3 1/2	3.500	11.660	139.92
3 3/4	3.750	13.390	160.68
4	4.000	15.230	182.76
4 1/4	4.250	17.030	204.36

Rounds

7075-T6, T651

AMS QQ-A-225/9, ASTM B221,

AMS 4122, AMS 4123

12' Lengths



SIZE	DEC	Approx WT. Per FT.	Approx WT. Per Length
4 1/2	4.500	18.710	224.52
4 3/4	4.750	20.840	250.08
5	5.000	23.100	277.20
5 1/2	5.500	27.950	335.40
6	6.000	33.260	399.12
7	7.000	46.210	554.52