


# Sheet

## 1100-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/1, ASTM B209,  
AMS 4001, AMS 4003



---

Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.040	36	96	.565	13.560
.050	36	96	.706	16.944
.063	36	96	.889	21.336
.125	48	144	1.764	84.672

# Sheet

## 3003-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4006, AMS 4008



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.016	36	96	.228	5.472
	36	120	.228	6.840
	36	144	.228	8.208
	48	96	.228	7.296
	48	120	.228	9.120
	48	144	.228	10.944
.020	36	96	.285	6.840
	36	120	.285	8.550
	36	144	.285	10.260
	48	96	.285	9.120
	48	120	.285	11.4000
	48	144	.285	13.680
.025	36	96	.356	8.544
	36	120	.356	10.680
	36	144	.356	12.816
	48	96	.356	11.392
	48	120	.356	14.240
	48	144	.356	17.088
.032	36	96	.456	10.944
	36	120	.456	13.680
	36	144	.456	16.416
	48	96	.456	14.592
	48	120	.456	18.240
	48	144	.456	21.888
.040	36	96	.570	13.680
	36	120	.570	17.100

# Sheet

## 3003-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4006, AMS 4008



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.040	36	144	.570	20.520
	48	96	.570	18.240
	48	120	.570	22.800
	48	144	.570	27.360
	60	96	.570	22.800
	60	120	.570	28.500
	60	144	.570	34.200
	.050	36	96	.713
36		120	.713	21.390
36		144	.713	25.668
48		96	.713	22.816
48		120	.713	28.520
48		144	.713	34.224
60		96	.713	28.520
60		120	.713	35.650
60		144	.713	42.780
.063		36	96	.898
	36	120	.898	26.940
	36	144	.898	32.328
	48	96	.898	28.736
	48	120	.898	35.920
	48	144	.898	43.104
	60	96	.898	35.920
	60	120	.898	44.900
	60	144	.898	53.880
	.080	36	96	1.140

# Sheet

## 3003-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4006, AMS 4008




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.080	36	120	1.140	34.200
	36	144	1.140	41.040
	48	96	1.140	36.480
	48	120	1.140	45.600
	48	144	1.140	54.720
	60	96	1.140	45.600
	60	120	1.140	57.000
	60	144	1.140	68.400
.090	36	96	1.283	30.792
	36	120	1.283	38.490
	36	144	1.283	46.188
	48	96	1.283	41.056
	48	120	1.283	51.320
	48	144	1.283	61.584
	60	96	1.283	51.320
	60	120	1.283	64.150
60	144	1.283	76.980	
.100	36	96	1.426	34.224
	36	120	1.426	42.780
	36	144	1.426	51.336
	48	96	1.426	45.632
	48	120	1.426	57.040
	48	144	1.426	68.448
	60	96	1.426	57.040
	60	120	1.426	71.300
60	144	1.426	85.560	

# Sheet

## 3003-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4006, AMS 4008




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.125	36	96	1.782	42.768
	36	120	1.782	53.460
	36	144	1.782	64.152
	48	96	1.782	57.024
	48	120	1.782	71.280
	48	144	1.782	85.536
	60	96	1.782	71.280
	60	120	1.782	89.100
	60	144	1.782	106.920
.190	36	96	2.709	65.016
	36	120	2.709	81.270
	36	144	2.709	97.524
	48	96	2.709	86.688
	48	120	2.709	108.360
	48	144	2.709	130.032
	60	96	2.709	108.360
	60	120	2.709	135.450
	60	144	2.709	162.540
.249	48	96	3.550	113.600
	48	120	3.550	142.000
	48	144	3.550	170.400

# Sheet

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/8, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.020	36	96	.279	6.696
	36	120	.279	8.370
	36	144	.279	10.044
	48	96	.279	8.928
	48	120	.279	11.160
	48	144	.279	13.392
.025	36	96	.349	8.376
	36	120	.349	10.470
	36	144	.349	12.564
	48	96	.349	11.168
	48	120	.349	13.960
	48	144	.349	16.752
.032	36	96	.447	10.728
	36	120	.447	13.410
	36	144	.447	16.092
	48	96	.447	14.304
	48	120	.447	17.880
	48	144	.447	21.456
.040	36	96	.559	13.416
	36	120	.559	16.770
	36	144	.559	20.124
	48	96	.559	17.888
	48	120	.559	22.360
	48	144	.559	26.832
	60	96	.559	22.360
	60	120	.559	27.950

# Sheet

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/8, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.040	60	144	.559	33.540
.050	36	96	.698	16.752
	36	120	.698	20.940
	36	144	.698	25.128
	48	96	.698	22.336
	48	120	.698	27.920
	48	144	.698	33.504
	60	96	.698	27.920
	60	120	.698	34.900
	60	144	.698	41.880
.063	36	96	.880	21.120
	36	120	.880	26.400
	36	144	.880	31.680
	48	96	.880	28.160
	48	120	.880	35.200
	48	144	.880	42.240
	60	96	.880	35.200
	60	120	.880	44.000
	60	144	.880	52.800
	72	96	.880	42.240
	72	120	.880	52.800
	72	144	.880	63.360
.080	36	96	1.117	26.808
	36	120	1.117	33.510
	36	144	1.117	40.212
	48	96	1.117	35.744

# Sheet

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/8, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.080	48	120	1.117	44.680
	48	144	1.117	53.616
	60	96	1.117	44.680
	60	120	1.117	55.850
	60	144	1.117	67.020
.090	36	96	1.257	30.168
	36	120	1.257	37.710
	36	144	1.257	45.252
	48	96	1.257	40.224
	48	120	1.257	50.280
	48	144	1.257	60.336
	60	96	1.257	50.280
	60	120	1.257	62.850
	60	144	1.257	75.420
.100	36	96	1.397	33.528
	36	120	1.397	41.910
	36	144	1.397	50.292
	48	96	1.397	44.704
	48	120	1.397	55.880
	48	144	1.397	67.056
	60	96	1.397	55.880
	60	120	1.397	69.850
	60	144	1.397	83.820
.125	36	96	1.746	41.904
	36	120	1.746	52.380
	36	144	1.746	62.856



# Sheet

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/8, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.125	48	96	1.746	55.872
	48	120	1.746	69.840
	48	144	1.746	83.808
	60	96	1.746	69.840
	60	120	1.746	87.300
	60	144	1.746	104.760
	72	96	1.746	83.808
	72	120	1.746	104.760
	72	144	1.746	125.712
.160	48	96	2.235	71.520
	48	120	2.235	89.400
	48	144	2.235	107.28
.190	36	96	2.654	63.696
	36	120	2.654	79.620
	36	144	2.654	95.544
	48	96	2.654	84.928
	48	120	2.654	106.160
	48	144	2.654	127.392
	60	96	2.654	106.160
	60	120	2.654	132.700
	60	144	2.654	159.240
	72	96	2.654	127.392
	72	120	2.654	159.240
	72	144	2.654	191.088
.250	36	96	3.492	83.808
	36	120	3.492	104.760

# Sheet

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/8, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017



---

Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.250	36	144	3.492	125.712
	48	96	3.492	111.744
	48	120	3.492	139.680
	48	144	3.492	167.616
	60	96	3.492	139.680
	60	120	3.492	174.600
	60	144	3.492	209.520
	72	96	3.492	167.616
	72	120	3.492	209.520
	72	144	3.492	251.424


# Sheet

2024-T3, 0

Bare

AMS QQ-A-250/4,

AMST B209, AMS 4037



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.016	48	144	.230	11.059
.020	48	144	.288	13.824
.025	48	144	.360	17.280
.032	48	144	.461	22.128
.040	48	144	.576	27.648
.050	48	144	.720	34.560
.063	48	144	.907	43.536
.071	48	144	1.022	49.056
.080	48	144	1.150	55.200
.090	48	144	1.300	62.400
.100	48	144	1.440	69.120
.125	48	144	1.800	86.400
.160	48	144	2.304	110.592
.190	48	144	2.740	131.52


# Sheet

**2024-T3, 0**

Alclad

AMS QQ-A-250/5,

ASTM B209, AMS 4041



---

Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.020	48	144	.288	13.824
.025	48	144	.360	17.280
.032	48	144	.461	22.128
.040	48	144	.576	27.648
.050	48	144	.720	34.560
.063	48	144	.907	43.536
.080	48	144	1.152	55.296
.090	48	144	1.300	62.400
.125	48	144	1.800	86.400

# Sheet

## 6061-T6, T4, 0

Mill Finish — Heat Treatable

AMS QQ-A-250/11, ASTM B209,

AMS 4027, AMS 4026, AMS 4025



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.016	48	144	.233	11.184
.020	48	144	.282	13.536
.025	48	144	.353	16.944
.032	48	144	.452	21.696
.040	48	144	.565	27.120
.050	48	120	.706	28.240
	48	144	.706	33.888
	60	144	.706	42.360
.063	48	120	.889	35.560
	48	144	.889	42.672
	60	144	.889	53.340
.080	48	120	1.127	45.080
	48	144	1.127	54.096
	60	144	1.127	67.620
.090	48	120	1.270	50.800
	48	144	1.270	60.960
	60	144	1.270	76.200
.100	48	120	1.411	56.440
	48	144	1.411	67.728
	60	144	1.411	84.660
.125	48	120	1.764	70.560
	48	144	1.764	84.672
	60	144	1.764	105.840
.160	48	144	2.254	108.192
.190	48	120	2.685	107.400
	48	144	2.685	128.880
	60	144	2.685	161.100


# Sheet

**7075-T6, O**

Bare

AMS QQ-A-250/12,

ASTM B209, AMS 4041



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.016	48	144	.230	11.050
.020	48	144	.291	13.970
.025	48	144	.364	17.470
.032	48	144	.466	22.370
.040	48	144	.582	27.940
.050	48	144	.727	34.890
.063	48	144	.916	43.970
.071	48	144	1.030	49.440
.080	48	144	1.162	55.780
.090	48	144	1.313	63.020
.100	48	144	1.454	69.790
.125	48	144	1.818	87.260
.160	48	144	2.323	111.500
.190	48	144	2.767	132.820


# Sheet

**7075-T6, O**

Alclad

AMS QQ-A-250/13,

ASTM B209, AMS 4041




---

Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.016	48	144	.230	11.050
.020	48	144	.291	13.970
.025	48	144	.364	17.470
.032	48	144	.466	22.370
.040	48	144	.582	27.940
.050	48	144	.727	34.890
.063	48	144	.916	43.970
.071	48	144	1.030	49.440
.080	48	144	1.162	55.780
.090	48	144	1.313	63.020
.100	48	144	1.454	69.790
.125	48	144	1.818	87.260

# Sheet

## Coilzak

### Specular Lighting Sheet




---

Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.025	24	96	.360	5.760
.032	24	96	.461	7.376



# Sheet (Coil & Sheet)



**3003**

Tread Brite

Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.
.063	48		1.020	
	48	96	1.020	32.64
	48	120	1.020	40.80
	48	144	1.020	48.96
	48	192	1.020	65.28
.100	48		1.570	
	48	96	1.570	50.24
	48	120	1.570	62.80
	48	144	1.570	75.36
	48	192	1.570	100.48
.125	48		1.920	
	48	96	1.920	61.44
	48	120	1.920	76.80
	48	144	1.920	92.16
	48	192	1.920	122.88
.125	60		1.920	
	60	96	1.920	76.80
	60	120	1.920	96.00
	60	144	1.920	115.20
	60	192	1.920	153.60
.188	48	120	2.820	112.80