


Channels


6061-T6 American Standard
 AMS QQ-A-200/16, ASTM B308,
 ASTM B221, AMS 4150
 25' Lengths



A (Inches)	B (Inches)	T1 (Inches)	Approx WT. Per FT.	Approx WT. Per Length
3.000	1.410	.170	1.418	35.450
	1.498	.258	1.729	43.225
	1.596	.356	2.070	51.750
4.000	1.580	.180	1.846	46.150
	1.647	.247	2.163	54.075
	1.720	.320	2.505	62.625
5.000	1.750	.190	2.316	57.900
	1.885	.325	3.110	77.750
	2.032	.472	3.974	99.350
6.000	1.920	.200	2.826	70.650
	1.945	.225	3.002	75.050
	2.034	.314	3.630	90.750
	2.157	.438	4.505	112.625
7.000	2.110	.230	3.542	88.550
8.000	2.290	.250	4.252	106.300
10.000	2.600	.240	5.279	131.975
12.000	2.960	.300	7.411	185.275
	3.170	.510	10.375	259.375

Channels

6061-T6 Aluminum Association
 AMS QQ-A-200/16, ASTM B308,
 ASTM B221, AMS 4150
 25' Lengths



A (Inches)	B (Inches)	T1 (Inches)	T2 (Inches)	Approx WT. Per FT.	Approx WT. Per Length
2.000	1.000	.130	.130	.577	14.425
	1.250	.170	.260	1.071	26.775
3.000	1.500	.130	.200	1.134	28.350
	1.750	.170	.260	1.597	39.925
4.000	2.000	.150	.230	1.738	43.450
	2.250	.190	.290	2.330	58.250
5.000	2.250	.150	.260	2.211	55.275
	2.750	.190	.320	3.089	77.225
6.000	2.500	.170	.290	2.834	70.850
	3.250	.210	.350	4.030	100.750
7.000	2.750	.170	.290	3.204	80.100
	3.500	.210	.380	4.714	117.850
8.000	3.000	.190	.350	4.146	103.650
	3.750	.250	.410	5.789	144.725
9.000	3.250	.230	.350	4.982	124.550
	4.000	.290	.440	6.970	174.250
10.000	3.500	.250	.410	6.136	153.400
	4.250	.310	.500	8.360	209.000
12.000	4.000	.290	.470	8.274	206.850
	5.000	.350	.620	11.822	295.550


Channels

6063-T52 Sharp Corners

AMS QQ-A-200/9,

ASTM B221

16' Lengths



A (Inches)	B (Inches)	T (Inches)	Approx WT. Per FT.	Approx WT. Per Length
.500	.750	.125	.257	4.128
.625	.625	.125	.239	3.782
.750	.750	.125	.294	4.704
1.000	.500	.125	.257	4.075
	1.000	.125	.207	6.464
1.250	1.250	.125	.514	8.258
1.500	1.000	.125	.478	7.792
1.750	.750	.125	.441	7.056
1.750	1.000	.125	.514	8.256
2.000	.500	.125	.404	6.480
	.750	.125	.478	7.792
	1.000	.125	.551	8.832
	2.000	.125	.845	13.392
	2.000	.250	1.617	36.740
2.250	.875	.125	.551	11.040
	1.500	.125	.772	12.232
3.000	.500	.125	.551	8.832
	1.000	.125	.698	11.184
4.000	1.000	.125	.836	13.376
5.000	2.000	.188	1.907	31.120