

# Coil

## 2024-T3, 0

Mill Finish — Heat Treatable

Bare: AMS QQ-A-250/4, AMS 4037,  
AMS 4035, ASTM B209



---

Decimal Thickness	Width	Approx WT. Per SQ. FT.
.016	48	.230
.020	48	.288
.025	48	.360
.032	48	.461
.040	48	.576
.050	48	.720
.063	48	.907
.080	48	1.152
.090	48	1.300
.100	48	1.440
.125	48	1.800

# Coil

## 6061-T6, T4, 0

Mill Finish — Heat Treatable

AMS QQ-A-250/11, ASTM B209,

AMS 4027, AMS 4026, AMS 4025



---

Decimal Thickness	Width	Approx WT. Per SQ. FT.
.012	48	.169
.016	48	.240
.020	48	.282
.025	48	.353
.032	48	.452
.040	48	.564
.050	48	.706
.063	48	.889
.080	48	1.129
.090	48	1.270
.100	48	1.411
.125	48	1.764
.160	48	2.258
.190	48	2.681

# Coil

## 3003-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4006, AMS 4008



Decimal Thickness	Width	Approx WT. Per SQ. FT.
.016	36	.228
	48	.228
.020	36	.285
	48	.285
.025	36	.356
	48	.356
.032	36	.456
	48	.456
.040	36	.570
	48	.570
	60	.570
.050	36	.713
	48	.713
	60	.713
.063	36	.898
	48	.898
	60	.898
.080	36	1.140
	48	1.140
	60	1.140
.090	36	1.283
	48	1.283
	60	1.283
.100	36	1.426
	48	1.426
	60	1.426

# Coil

## 3003-H14, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4006, AMS 4008



---

Decimal Thickness	Width	Approx WT. Per SQ. FT.
.125	36	1.782
	48	1.782
	60	1.782
	72	1.782
.190	36	2.709
	48	2.709
	60	2.709
	72	2.709
.249	48	3.550
	60	3.550

# Coil

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017



Decimal Thickness	Width	Approx WT. Per SQ. FT.
.020	36	.279
	48	.279
.025	36	.349
	48	.349
.032	36	.447
	48	.447
.040	36	.559
	48	.559
	60	.559
.050	36	.698
	48	.698
	60	.698
.063	36	.880
	48	.880
	60	.880
.080	36	1.117
	48	1.117
	60	1.117
.090	36	1.257
	48	1.257
	60	1.257
.100	36	1.397
	48	1.397
	60	1.397
.125	36	1.746
	48	1.746

# Coil

## 5052-H32, H34, 0

Mill Finish — Non-Heat Treatable  
AMS QQ-A-250/2, ASTM B209,  
AMS 4015, AMS 4016, AMS 4017



---

Decimal Thickness	Width	Approx WT. Per SQ. FT.
.125	60	1.746
	72	1.746
.160	36	2.235
	48	2.235
	60	2.235
.190	36	2.654
	48	2.654
	60	2.654
	72	2.654
.249	36	3.478
	48	3.478
	60	3.478
	72	3.478

# Coil & Sheet

3003, 3004, 3105, 5052

Painted 1 side & 2 sides



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SHT.	Painted 2 Sides
.032	48		.465		*
	48	96	.465	14.880	*
	48	120	.465	18.600	*
	48	144	.465	22.320	*
.040	48		.578		*
	48	96	.578	18.496	*
	48	120	.578	23.120	*
	48	144	.578	27.744	*
.050	48		.706		*
	48	96	.706	22.592	*
	48	120	.706	28.240	*
	48	144	.706	33.888	*
.050	49		.706		
	49	96	.706	23.063	
	49	120	.706	28.828	
	49	144	.706	34.594	
.063	48		.880		*
	48	96	.880	28.160	*
	48	120	.880	35.200	*
	48	144	.880	42.240	*
.080	48	96	1.116	35.712	
	48	120	1.116	44.640	